

## HOT AIR BLOWER & MIXING FAN



TYPE HHB		40	70	80	120
Rated Load	kW	40	70	80	120
	K.cal.	34.300	60.200	86.000	103.200
	Btu	136.136	238.910	341.300	409.560
Gas consumpt. (Nat.)	m <sup>3</sup> /h	4,3	7,5	10,8	13,00
Gas consumpt. (Prop.)	kg/h	2,9	5,4	6,5	8,1
Airmovement	m <sup>3</sup> /h	3000	5000	6500	6500
Electric consumption	Amp.	1,3	1,8	2,75	2,75
Revolution speed	R. p/m	1330	1400	1400	1400
Weight	Kilo	32	42	48	48

TYPE HHB		8 LTR	10 LTR	12 LTR
Rated Load	kW	80	100	120
	K.cal.	68000	86000	103000
Consumption oil	L. p/h	8	10	12
Air movement	m <sup>3</sup> p/h	7700	7700	7700
Air throw	metre	45	45	45
Electric consumption	Amp.	3,5	3,5	3,7
Revolution speed	R. p/m	1400	1400	1400
Weight	Kilo	55	55	65

## RADIANT (INFRARED) HEATING SYSTEM



MODEL	Operation Pressure mbar	Capacity kcal/h	Capacity watt/h	Gas Consumption gr/h	Weight kg
AP2 Heater	20-1000	500-4300	580-5000	36-360	1,50

## SOLID FUEL (COIL) HEATER

Capacity kcal/h	Motor Power Hp	Fan Flow m <sup>3</sup> /h	Air Flow m <sup>3</sup> /h	Air Flow Temperature °C
150.000	4	12.000	8.000	120
250.000	5.5	18.000	12.000	
300.000	5.5	18.000	12.000	
500.000	5.5	40.000	26.650	

